

Multifunction Hydraulic Fluid for power steering, hydraulic dampers, suspensions, hard top and hydraulic central systems. SYNTHETIC

TYPE OF USE

Multifunction high performance synthetic based Hydraulic Fluid specially developed for recent vehicles fitted with hydraulic systems such as power steering, hydraulic dampers and hydraulic hard top.

This product is particularly recommended to be use with the following European OEM's: VW (VAG), AUDI, PORSCHE, BMW, CITROËN, MERCEDES, MINI, PEUGEOT, VOLVO, SAAB and American: FORD, GENERAL MOTORS-OPEL.

Do not use in gearbox.

PERFORMANCES

MOTUL MULTI HF is a high technology lubricant with outstanding performances thanks to its exclusive and dedicated formula which:

- Protects hydraulic pumps heavily loaded.
- Extends life time duration of all systems.
- Provide comfort and noise reduction especially at cold conditions.
- Provide outstanding anti-wear, anti-corrosion and anti-foam properties

RECOMMENDATIONS

Can be mixed with similar hydraulic lubricants.

Do not use in manual or automatic gearboxes.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.823
Viscosity at 40°C (104°F)	ASTM D445	19.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	6.2 mm²/s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MULTI HF

**Multifunction Hydraulic Fluid for power steering, hydraulic dampers, suspensions, hard top and hydraulic central systems.
SYNTHETIC**

Viscosity Index	ASTM D2270	328.0
Flash point	ASTM D92	155.0 °C / 311.0 °F

Multifunction Hydraulic Fluid for power steering, hydraulic dampers, suspensions, hard top and hydraulic central systems. SYNTHETIC

STANDARDS	
DIN	51 524 T2, 51 524 T3
OE PERFORMANCES	
AUDI	TL 52 146, G 002 000, G 00 4000
BENTLEY	RH 5000, TH 5000
BMW	81 22 9 407 758, 82 11 0 148 132, 82 11 1 468 041, 83 29 0 429 576
CHRYSLER	MS 10838, MS 11655, MS 5931
CITROËN	9730 A5, 99 7969, 9979 A4, H 50126, Total Fluide DA, Total Fluide LDS
DS (CAPSA)	9730 A5, 99 7969, 9979 A4, H 50126, Total Fluide DA, Total Fluide LDS
FENDT	X 902 011 622
FIAT	9.55550-SA1, Tutela GI/R
FORD	WSS M2C 204 A
FUCHS	TITAN ZH 3044, TITAN ZH 4300 B
GENERAL MOTORS	B 040 0070, GM 1940715, GM 1940766
MAN	M 3289 (3623/93)
MERCEDES-BENZ	001 989 24 03 10, 001 989 24 03 12, MB 345.0, Q 1 32 0001
MINI	81 22 9 407 758, 82 11 0 148 132, 82 11 1 468 041, 83 29 0 429 576
PEUGEOT	9730 A5, 99 7969, 9979 A4, H 50126, Total Fluide DA, Total Fluide LDS
PORSCHE	000 043 203 33, 000 043 206 56
SAAB	3032 380
VOLVO	1161529
VW	G 002 000, G 004 000, TL 52 146
ZF	TE-ML 02K
PRODUCTS	
AGIP	CHF
CASTROL	CHF
CHEVRON	PSF 9109
FUCHS	TITAN ZH 3044, TITAN ZH 4300 B
IGOL	BLOCK DA
MOPAR PARTS	MS 11655
PENTOSIN	CHF 11S, CHF 202
PETRONAS LUBRICANTS	Tutela CS Speed, Tutela GI/R
PSA Groupe	9730 A5, 99 7969, 9979 A4, H 50126, Total Fluide DA, Total Fluide LDS
SELENIA	Tutela CS Speed, Tutela GI/R
TEXACO	PSF 9109

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MULTI HF

**Multifunction Hydraulic Fluid for power steering, hydraulic dampers, suspensions, hard top and hydraulic central systems.
SYNTHETIC**

TOTAL	Fluide DA, Fluide LDS
UNIL-OPAL	LDA
ZF	TE-ML 02K