

MOTUL**8100 X-CLEAN+ 5W-30****DPF****Gasoline & diésel lubricant - Euro 4, 5 & 6**
100% Synthetic**TYPE OF USE**

High performance 100% Synthetic lubricant specially designed for latest generation of diésel and Gasoline engines, Euro 4, 5 or 6 emission regulation compliant, requiring an engine oil with high HTHS ($> 3.5 \text{ mPa.s}$) viscosity and "Mid SAPS" with reduced content of Sulfated Ash ($\leq 0.8\%$), Phosphorus ($0.07\% \leq x \leq 0.09\%$) and Sulfur ($\leq 0.3\%$). Compatible with catalytic converters (CAT) and diésel Particulate Filters (DPF). Particularly suitable for the latest generation of BMW, MERCEDES, PORSCHE and VAG (VW, AUDI, SEAT, SKODA) vehicles.

Suitable also for any type of diésel or Gasoline engines calling for ACEA C3 lubricant.

Before use always refer to the owner manual or handbook of the vehicle.

PERFORMANCES

STANDARDS ACEA C3

APPROVALS BMW LL-04
 MERCEDES-BENZ MB-Approval 229.51
 PORSCHE C30
 VW 504 00 507 00

Engines compliant with Euro 4, 5 and 6 emission regulation are fitted with sensitive exhaust gas after treatment systems. Indeed, Sulfur and Phosphorus inhibit catalytic converters operation leading to inefficient exhaust gas treatment; and Sulfated Ashes clog DPFs leading to shorten regenerating cycle, quick oil aging, higher fuel consumption and engine power loss.

The BMW Long Life-04 specification imposes severe constraints to the lubricant particularly due to Valvetronic and after treatment systems compatibility. It covers all BMW engines from 2004 and also all BMW engines before 2004. BMW LL-04 covers all the previous BMW specifications such as BMW LL-98 and BMW LL-01. ATTENTION: BMW LL-04 product can be used for gasoline engines only in European Union countries, Switzerland, Norway and Liechtenstein. Outside those countries, a BMW LL-01 lubricant such as MOTUL 8100 X-cess gen2 5W-40 is required. Refer to BMW recommendations when in doubt. MOTUL 8100 X-clean+ 5W-30 fulfils all the specifications of BMW Long Life-04 standard of the BMW Group for BMW, MINI and ROLLS-ROYCE vehicles with no exceptions i.e. for models before 2019 and after 2019. For models up to 2019, i.e. until end of 2018 only, MOTUL 8100 X-clean 5W-40 can also be used.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

03/21

The MB 229.51 requires among many other severe constrains from the lubricant a reduced content of Sulfated Ash, Phosphorus and Sulphur in order to be compatible with MERCEDES exhaust gas after treatment systems. These oils can reach flexible drain intervals managed by computer on board due to outstanding shear resistance properties. The specification MB 229.51 applies to some MERCEDES Gasoline engines, and to all MERCEDES diésel engines, with or without DPF.

PORSCHE has introduced its C30 norm to guarantee the perfect lubrication of all their diésel engines and V6 Gasoline engines (Porsche Cayenne). Approved "PORSCHE C30" lubricant fulfills all these highly demanding requests especially regarding oil film resistance.

VOLKSWAGEN for their VW 504 00 and VW 507 00 standards requires from the lubricant to be fully compatible with their after treatment systems such as catalytic converters and DPFs to ensure the highest durability of most Gasoline and diésel engines of VW, AUDI, SEAT and SKODA vehicles.

MOTUL 8100 X-clean+ 5W-30 fully answer all those various requests that BMW, MERCEDES, PORSCHE and VW have developed for their lubricant standards through engine oils with high HTHS (> 3.5 mPa.s), reduced Sulfated Ash, Phosphorus and Sulfur content (Mid SAPS), suitable for use with modern exhaust gas after treatment systems.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic and mineral oils.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	69.2 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	11.8 mm²/s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.5 mPa.s
Viscosity Index	ASTM D2270	167.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



8100 X-CLEAN+ 5W-30

DPF

Gasoline & diésel lubricant - Euro 4, 5 & 6
100% Synthetic

Sulfated Ash	ASTM D874	0.68 % weight
TBN	ASTM D2896	6.7 mg KOH/g
Flash point	ASTM D92	226.0 °C / 439.0 °F